

200 H.O.

Engine Model	E200LH E200LHO E200XH E200XHC
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke - mm (in.)	98 x 76 (3.854 x 3.000)
Displacement - cc (cu. in.) L	3,441 (210) 3.4 L
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg (lb.)*	244 (539)
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	133 Amps Total 50 net Dedicated 14 Amps @ idle
Steering	Remote
Trim Method	Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - mm (in.)	508 (20) 635 (25)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L (US gal.)	On-Engine 7.5 (2) Accessory 6.8 (1.8) & 11.3 (3)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty‡	5-Year, Non-Declining¹ 5-Year Corrosion
Emissions Compliance	EPA 2013 CARB 3 STAR European Union
Mounting Centers - mm (in.)	Minimum 711 (28)***
Color	Slate Gray with over 400 Color Panel Options
Steering Angle	+/- 32°
Integrated Features	Dynamic Power Steering¹ Hydraulic Steering Dual Axis Rigging i-Trim



* Dry weight for the lightest model/version of each horsepower listed in that grouping.
 ** Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.
 *** Multi-rigged boats only.
 † On equipped models.
 ‡ Available in selected markets. Please contact your authorised Evinrude dealer for details.

225 HP

Engine Model	E225X E225XC
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke - mm (in.)	98 x 76 (3.854 x 3.000)
Displacement - cc (cu. in.) L	3,441 (210) 3.4 L
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg (lb.)*	253 (558)
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	133 Amps Total 50 net Dedicated 14 Amps @ idle
Steering	Remote
Trim Method	Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - mm (in.)	508 (20) 635 (25) 762 (30)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L (US gal.)	On-Engine 7.5 (2) Accessory 6.8 (1.8) & 11.3 (3)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty‡	5-Year Engine‡ 5-Year Corrosion
Emissions Compliance	EPA 2013 CARB 3 STAR European Union
Mounting Centers - mm (in.)	Minimum 711 (28)***
Color	Slate Gray with over 400 Color Panel Options
Steering Angle	+/- 32°
Integrated Features	Dynamic Power Steering† Hydraulic Steering Dual Axis Rigging i-Trim



* Dry weight for the lightest model/version of each horsepower listed in that grouping.
 ** Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.
 *** Multi-rigged boots only.
 † On equipped models.
 ‡ Available in selected markets. Please contact your authorised Evinrude dealer for details.

225 H.O.

Engine Model	E225LH E225XH E225LHO
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke - mm (in.)	98 x 76 (3.854 x 3.000)
Displacement - cc (cu. in.) L	3,441 (210) 3.4 L
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg (lb.)*	244 (539)
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	133 Amps Total 50 net Dedicated 14 Amps @ idle
Steering	Remote
Trim Method	Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - mm (in.)	508 (20) 635 (25)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L (US gal.)	On-Engine 7.5 (2) Accessory 6.8 (1.8) & 11.3 (3)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty†	5-Year Engine‡ 5-Year Corrosion
Emissions Compliance	EPA 2013 CARB 3 STAR European Union
Mounting Centers - mm (in.)	Minimum 711 (28)***
Color	Slate Gray with over 400 Color Panel Options
Steering Angle	+/- 32°
Integrated Features	Dynamic Power Steering† Hydraulic Steering Dual Axis Rigging i-Trim



* Dry weight for the lightest model/version of each horsepower listed in that grouping.

** Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

*** Multi-rigged boats only.

† On equipped models.

‡ Available in selected markets. Please contact your authorised Evinrude dealer for details.

250 HP

Engine Model	250X E250Z E250XC E250ZC
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke - mm (in.)	98 x 76 (3.854 x 3.000)
Displacement - cc (cu. in.) L	3,441 (210) 3.4 L
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg (lb.)*	253 (558)
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	133 Amps Total 50 net Dedicated 14 Amps @ idle
Steering	Remote
Trim Method	Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - mm (in.)	508 (20) 635 (25) 762 (30)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L (US gal.)	On-Engine 7.5 (2) Accessory 6.8 (1.8) & 11.3 (3)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty†	5-Year Engine† 5-Year Corrosion
Emissions Compliance	EPA 2013 CARB 3 STAR European Union
Mounting Centers - mm (in.)	Minimum 711 (28)***
Color	Slate Gray with over 400 Color Panel Options
Steering Angle	+/- 32°
Integrated Features	Dynamic Power Steering† Hydraulic Steering Dual Axis Rigging i-Trim



* Dry weight for the lightest model/version of each horsepower listed in that grouping.

** Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

*** Multi-rigged boots only.

† On equipped models.

‡ Available in selected markets. Please contact your authorised Evinrude dealer for details.

250 H.O.

Engine Model	E250LH E250XH E250LHO
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke - mm (in.)	98 x 76 (3.854 x 3.000)
Displacement - cc (cu. in.) L	3,441 (210) 3.4 L
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg (lb.)*	244 (539)
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	133 Amps Total 50 net Dedicated 14 Amps @ idle
Steering	Remote
Trim Method	Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - mm (in.)	508 (20) 635 (25)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L (US gal.)	On-Engine 7.5 (2) Accessory 6.8 (1.8) & 11.3 (3)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty†	5-Year Engine‡ 5-Year Corrosion
Emissions Compliance	EPA 2013 CARB 3 STAR European Union
Mounting Centers - mm (in.)	Minimum 711 (28)***
Color	Slate Gray with over 400 Color Panel Options
Steering Angle	+/- 32°
Integrated Features	Dynamic Power Steering† Hydraulic Steering Dual Axis Rigging i-Trim



* Dry weight for the lightest model/version of each horsepower listed in that grouping.

** Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

*** Multi-rigged boots only.

† On equipped models.

‡ Available in selected markets. Please contact your authorised Evinrude dealer for details.

300 HP

Engine Model	E300LU E300XU E300XCU E300ZU E300ZCU
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke - mm (in.)	98 x 76 (3.854 x 3.000)
Displacement - cc (cu. in.) L	3,441 (210) 3.4 L
Gear Ratio	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight - kg (lb.)*	253 (558)
Starting	Electric
Controls	Integrated Digital Shift & Throttle
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	133 Amps Total 50 net Dedicated 14 Amps @ idle
Steering	Remote
Trim Method	Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - mm (in.)	508 (20) 635 (25) 762 (30)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - L (US gal.)	On-Engine 7.5 (2) Accessory 6.8 (1.8) & 11.3 (3)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty‡	5-Year Engine‡ 5-Year Corrosion
Emissions Compliance	EPA 2013 CARB 3 STAR European Union
Mounting Centers - mm (in.)	Minimum 711 (28)***
Color	Slate Gray with over 400 Color Panel Options
Steering Angle	+/- 32°
Integrated Features	Dynamic Power Steering† Hydraulic Steering Dual Axis Rigging i-Trim



* Dry weight for the lightest model/version of each horsepower listed in that grouping.
 ** Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.
 *** Multi-rigged boats only.
 † On equipped models.
 ‡ Available in selected markets. Please contact your authorised Evinrude dealer for details.